SIMPLIFY CONSTRUCTION WITH PRECAST METHODOLOGY

It also enables earlier occupancy and reduced financing costs. If planned really well, it is like "Just-In-Time" where once you have completed your foundation or whilst the foundation is being done, the precast manufacturer has already started production of the precast concrete units in the factory." he said.

By: R.G. Candiah

The precast concrete industry in Malaysia is growing at a rapid pace due to the continuing usage of precast concrete being of consistent quality, economical, flexible and relable. Despite being adopted for many years now, smaller for many years now, smaller contractors are still ignorant of the advantages of precast concrete.

Precast concrete is defined as concrete components (for example, wall panels) of a building which are fabricated in a factory and then transported to the site of construction.

According to A. Letchumanan, Senior Manager of the Technical Department at the operating company of ACP Industries Berhad, contractors currently

prefer using precast concrete as opposed to cast in-situ as it brings numerous adventages. The adventages include durability, time saving, less wet work and a cleaner and safer work site due to a much reduced necessity for falseworks.

Precast concrete will provide more reliable long-term performance in externetly hanh conditions that could destroy lesser materials. In comparison to the traditional method of building, precast concrete is more resistant to deterioration from weather extremes, chemical attack, tine, accidental damage and the determined efforts of vandals.

Letchumanan said precasting concrete in a factory environment



allows the manufacturer to exercise precise control over all the variables, which affect durability, strength and appearance. Dense impermeable concrete can be readily produced at the factory by carefully controlling the materials, slump, water/cement ratio and the curing process.

"Precast concrete components lead themselves to fast construction schedules. Precast manufacturing can proceed in advance while site can be delivered to the jobsite and installed the moment they are needed in any weather, be said adding that fast construction means earlier completion after resulting cost savings. "If, for instance, a drainage structure in the middle of the to be diverted. Furthermore, the contractors will have to wait long hours before they can open the given road," he said adding that in-situ concrete generally needed a duration of 1-2 weeks for maturing.

According to Letchmamman, the usage of precast concrete is quite mature in Malaysia where infrastructure and the building sector are concerned built it is still in its infrancy stages in other areas of construction. He said the railway industry too was gradually adopting the usage of precast concrete.

The double tracking project from Rawang to Ipoh uses prestressed concrete skeepers and cable troughs. Precast manufacturers in Mataysia are currently producing approximately 700,000 skeepers for this project and demand is expected to continue.

Letchumanan said transportation was one of the constraints in the precast industry as road conditions and looistics governed it.

Precast concrete products can be transported if the size and proportions of the precast product fits the transport vehicle.

"Precast products are confined by the length of the trailer while the width has to be approximately 2.4m," he said adding that if items were to big, it would be split up into a few segments and then jointed together at the construction site.

He said there was a need to standardise the units or products as standard structural shapes such as precast culverts, floor double tees, bridge beams, box girders and wall panels can be mass-produced at low cost.

"We can re-use the mould again and again and this will benefit the end user with lower cost. Once a different size is requested, it then becomes "tailor-made" which becomes more expensive, unless volume justifies", he said.

Standardisation would also enable

contractors to benefit from ready stock in the factory.

Lebchumanan said manufacturers of precast concrete were moving more towards mechanisation requiring less labour but stressed that standardisation of precast concrete products was important in order to mechanise and automate the manufacturing process.

He added that precast concrete was better manufactured in a factory due to dedicated facilities instead of on-site in order to control quality and workmanship test of product prior to delivery.

"Many contractors want to do precast on-site as it is cheaper benefiting from lesser transport cost and nil sales tax," he said adding that casting on site was risky as there is no stringent requirements as to quality control.

In a factory controlled environment, precasters can implement good manufacturing practices, which ensures quality and tulfils customer satisfaction.

Security with Technology





Magnetic Control Systems Sch Bhd No. 16, Jalan Kartunis U1/47 Section U1, Temasya Industrial Park 40150 Shah Alam, Malaysia

Phone: + 60 3 5569 1718 Fax: + 60 3 5569 1719 Email: info@magnetic.com.my Web: www.ac-magnetic.com www.heras.com Magnetic offers unique peripheral security solutions for the security of buildings, premises and complexes. Magnetic works on a turnikey basis, from design to aftercare. Our strength is our dedication to innovation and service.

Security concepts are developed around the following elements: Fencing, Perimeter Detection and Access Control.



Magnetic will be presenting the Delta Gate pictured here, a robust but elegant cantilever structure, which has won prestigious industrial design awards, at Malbex 2004

21-24 September, MINES Exhibition Centre, Kuala Lumpur. Please visit booth S10.

