

## A Fitted Numerical Method for a Class of Singularly Perturbed Convection Delayed Dominated Diffusion Equation

Rakesh Ranjan<sup>1\*</sup>, H. S. Prasad<sup>1</sup> and Md. J. Alam<sup>1</sup>

<sup>1</sup>Department of Mathematics, National Institute of Technology Jamshedpur-14, India.

### ABSTRACT

*A new exponentially fitted numerical method based on uniform mesh is proposed to obtain the solution of a class of singularly perturbed convection delayed dominated diffusion equation. The considered equation is first reduced to the ordinary singularly perturbed problem by expanding the term containing negative shift using Taylor series expansion procedure and then a three-term scheme is obtained using the theory of finite differences. A fitting factor is introduced in the derived scheme with the help of singular perturbation theory. Thomas algorithm is employed to find the solution of the resulting tridiagonal system of equations. Stability and convergence of the proposed method are discussed. The method is shown to be first accurate. Computational results for two example problems are presented for different values of the grid point,  $N$  and perturbation parameter,  $\varepsilon$ . It is observed that the method is capable of approximating the solution very well.*

**Keywords:** Differential-Difference Equations, Exponential Fitting Factor, Finite Difference, Singular Perturbations, Stability and Convergence of Numerical Methods.

### 1. INTRODUCTION

Any system involving feedback control mostly involve time delays because a finite time is required to sense information and then react to it. The study of theoretical and applied problems in science and engineering leads to the boundary value problems for singularly perturbed differential equations with at least one delay (negative shift) and/or advance (positive shift) term. These equations are of multi-scale character in general. That is, there is thin transition layer(s) where solution varies most rapidly while away from the layers(s) solution behaves regularly and varies slowly. These singularly perturbed problems occur very frequently in modelling various real-life applications. Some of the applications of these problems can be found in high-level monographs and the articles: Rihan [1], Stein [2-3], Longtin and Milton [4], Derstine *et al.* [5], Bocharov and Rihan [6], Nelson and Perelson [7], Mackey and Glass [8], O'Malley [9,16], Knowles and Messick [10], Gold [11], Kaushik [12], Kaushik and Sharma [13], Kadalbajoo and Sharma [14], Kaushik [15], and Miller [17].

Developing efficient numerical methods for solving such singularly perturbed problems is challenging due to the existence of boundary and/or interior layers. Standard discretization techniques are unable to provide accurate results when the delay and/or advance parameter is/are small/big order of perturbation parameter. Singular perturbation analysis of boundary value problems for differential-difference equation with small shifts was initiated by Lange and Miura [18-20]. In the recent past, various numerical approaches have been suggested as the solution to such problems. The authors, Kadalbajoo and Sharma [21] gave an  $\varepsilon$ -uniform fitted operator method for solving boundary-value problems for singularly perturbed delay differential equations with layer behaviour. Kadalbajoo and Sharma [22] devised a numerical technique based on finite differences for solving singularly perturbed differential-difference equations.

---

\*Corresponding Author: 90.ranjan@gmail.com

Sharma *et al.* [23] suggested a way of analytic approximation to delayed convection dominated systems through transforms. Swamy *et al.* [24] presented a computational method for singularly perturbed delay differential equations (SPDDE) with twin layers or oscillatory behaviour. Numerical treatment for singularly perturbed convection delayed dominated diffusion equation via tension splines was presented in Kanth and Kumar [25]. File *et al.* [26] proposed a fourth-order finite difference method for finding the solution of SPDDE. Chakravarthy and Kumar [27] suggested a novel method based on Numerov's difference scheme for the solution of singularly SPDDE of reaction-diffusion type. Sirisha and Reddy [28] proposed an exponential fitted numerical integration technique for the solution of SPDDE. An extension of a fitted finite difference method for third-order SPDDE of convection-diffusion type is presented by Mahendran and Subburayan [29]. Kanth and Kumar [30] proposed a parametric spline scheme for a class of nonlinear SPDDE. The solution of second-order SPDDE using Trigonometric B-Spline was suggested by Vaid and Arora [31]. In this paper, we have suggested a new fitted numerical method based on uniform mesh for solving singularly perturbed convection delayed dominated diffusion equation. The paper is arranged as follows: statement of the considered problems with the description of the proposed methods is presented in Section 2, stability and convergence of the method is investigated in Section 3, and numerical illustrations are given in Section 4. Finally, the discussions and conclusions are presented in Section 5.

## 2. PROBLEM STATEMENT

Consider a class of singularly perturbed differential-difference equation of the form:

$$\varepsilon y''(x) + a(x)y'(x) + q(x)y(x - \delta) = f(x) \text{ on } \Omega = [0,1], \quad (1)$$

subject to the interval and boundary conditions:

$$y(x) = \eta(x) \text{ on } \delta \leq x \leq 0, y(1) = \gamma, \quad (2)$$

where  $0 < \varepsilon \ll 1$  is a perturbation parameter and  $\delta = o(\varepsilon)$  is a small shifting parameter. Furthermore  $a(x), q(x), f(x)$  and  $\eta(x)$  are sufficiently smooth functions in  $[0, 1]$  where  $\gamma$  is a constant. The equation (1) reduces to a singularly perturbed ordinary differential equation when  $\delta = 0$ , and the corresponding problem has a boundary layer on the left side for  $a(x) > 0$  or on the right side for  $a(x) < 0$  on  $[0,1]$ .

Using Taylor series expansion for the delayed term obtained from (1);

$$\varepsilon y''(x) + p(x)y'(x) + q(x)y(x) = f(x) \text{ on } \Omega = [0,1], \quad (3)$$

subject to the boundary conditions:

$$y(x) = \eta_0 \text{ and } y(1) = \gamma \quad (4)$$

where,  $p(x) = \{a(x) - \delta q(x)\}$ . Under the assumption that  $p(x) \geq M > 0$  throughout the interval  $[0,1]$ , where  $M$  is a positive constant, the problem (3) with (4) exhibits boundary layer at  $x = 0$ . Similarly when  $p(x) \leq M < 0$  throughout the interval  $[0,1]$ , where  $M$  is a negative constant, then the problem (3) with (4) exhibits boundary layer at  $x = 1$ .

Here, the operator  $L_\tau = \varepsilon \frac{d^2}{dx^2} + p(x) \frac{d}{dx} + q(x)I$  in (3) satisfies the following minimum principle.

**Lemma 1.** Suppose  $\psi(x)$  is a smooth function satisfying  $\psi(0) \geq 0, \psi(1) \geq 0$ . The  $L_\tau \psi(x) \leq 0, \forall x \in (0,1)$  implies  $\psi(x) \geq 0, \forall x \in [0,1]$ .

**Proof.** We can prove the above lemma by the method of contradiction. Let  $k \in [0,1]$  be such that  $\psi(k) < 0$  and  $\psi(k) = \min_{x \in [0,1]} \psi(x)$ . Clearly for  $k \notin \{0,1\}$ , we have  $\psi'(k) = 0$  and  $\psi''(k) \geq 0$ . Therefore, we obtain

$$L_\tau \psi(k) = \varepsilon \psi''(k) + p(k) \psi'(k) + q(k) \psi(k) > 0,$$

which is a contradiction to our assumption. Hence it is proved that  $\psi(k) \geq 0$  and thus  $\psi(x) \geq 0, \forall x \in [0,1]$ .

**Lemma 2.** Let  $y(x)$  be the solution of the problem (3) and (4) then we have

$$\|y\| \leq \theta^{-1} \|f\| + \max(|\eta_0|, |\gamma|). \quad (5)$$

where  $\|\cdot\|$  is the  $L_\infty$  norm given by  $\|y\| = \max_{0 \leq x \leq 1} |y(x)|$ .

**Proof.** Let  $\psi^\pm(x)$  be two barrier functions define by

$$\psi^\pm(x) = \theta^{-1} \|f\| + \max(|\eta_0|, |\gamma|) \pm y(x).$$

Then this implies,

$$\begin{aligned} \psi^\pm(0) &= \theta^{-1} \|f\| + \max(|\eta_0|, |\gamma|) \pm y(0) = \theta^{-1} \|f\| + \max(|\eta_0|, |\gamma|) \pm \eta_0 \text{ since } y(0) = \eta(0) = \eta_0 \geq 0, \\ \psi^\pm(1) &= \theta^{-1} \|f\| + \max(|\eta_0|, |\gamma|) \pm y(1) = \theta^{-1} \|f\| + \max(|\eta_0|, |\gamma|) \pm \gamma \text{ since } y(1) = \gamma \geq 0 \\ \Rightarrow L_\tau \psi^\pm(x) &= \varepsilon (\psi^\pm(x))'' + p(x) (\psi^\pm(x))' + q(x) \psi^\pm(x) = q(x) [\theta^{-1} \|f\| + \max(|\eta_0|, |\gamma|)] \pm L_\tau y(x) \\ &= q(x) [\theta^{-1} \|f\| + \max(|\eta_0|, |\gamma|)] \pm f(x) \text{ using (3)}. \end{aligned}$$

As  $q(x) \leq -\theta < 0$  implies  $q(x)\theta^{-1} \leq -1$  and since  $\|f\| \geq f(x)$ , we have

$$L_\tau \psi^\pm(x) \leq (-\|f\| \pm f(x)) + q(x) \max(|\eta_0|, |\gamma|) \leq 0, \forall x \in [0,1].$$

Thus, by the minimum principle, we obtain,  $\psi^\pm \geq 0, \forall x \in [0,1]$ , which gives the required estimate.

## 2.1. Description of the method for left-End Boundary Layer Problems

To describe the method, we consider the singularly perturbed boundary value problem (3)-(4) with  $p(x) \geq M > 0$ . The theory of singular perturbation gives the solution of (3) with (4) which is of the form [cf.[9], pp.22-26):

$$y(x) = y_0(x) + \frac{p(0)}{p(x)} (\alpha - y_0(0)) e^{-\int_0^x \left( \frac{p(x) - q(x)}{\varepsilon p(x)} \right) dx} + o(\varepsilon), \quad (6)$$

where  $y_0(x)$  is the solution of the reduced problem:

$$p(x)y_0'(x) + q(x)y_0(x) = f(x); y_0(1) = \beta. \quad (7)$$

Under the consideration of Taylor's series expansions of  $p(x)$  and  $q(x)$  about the point ' $x=0$ ' up to their first terms only, the equation (6) becomes:

$$y(x) = y_0(x) + (\alpha - y_0(0)) e^{-\left( \frac{p(0) - q(0)}{\varepsilon p(0)} \right) x} + o(\varepsilon). \quad (8)$$

Further, considering equation (5) at the point  $x = x_i = ih, i = 0, 1, 2, \dots, N$  and taking the limit as  $h \rightarrow 0$  we obtain

$$\lim_{h \rightarrow 0} y(ih) = y_0(0) + (\alpha - y_0(0)) e^{-\left( \frac{p^2(0) - \varepsilon q(0)}{p(0)} \right) i\rho} + o(\varepsilon), \quad (9)$$

where  $\rho = h / \varepsilon$ .

Assuming that  $y(x)$  is continuously differentiable in the interval  $[0, 1]$  and applying Taylor's series expansion for  $y(x_{i+1})$  and  $y(x_{i-1})$ , we have:

$$y(x_{i+1}) = y_{i+1} = y_i + hy_i' + \frac{h^2}{2!} y_i'' + \frac{h^3}{3!} y_i''' + \frac{h^4}{4!} y_i^{(4)} + \frac{h^5}{5!} y_i^{(5)} + \frac{h^6}{6!} y_i^{(6)} + \frac{h^7}{7!} y_i^{(7)} + \frac{h^8}{8!} y_i^{(8)} + O(h^9) \quad (10)$$

$$y(x_{i-1}) = y_{i-1} = y_i - hy_i' + \frac{h^2}{2!} y_i'' - \frac{h^3}{3!} y_i''' + \frac{h^4}{4!} y_i^{(4)} - \frac{h^5}{5!} y_i^{(5)} + \frac{h^6}{6!} y_i^{(6)} - \frac{h^7}{7!} y_i^{(7)} + \frac{h^8}{8!} y_i^{(8)} - O(h^9). \quad (11)$$

From finite differences, we have

$$y_{i-1} - 2y_i + y_{i+1} = \frac{2h^2}{2!} y_i'' + \frac{2h^4}{4!} y_i^{(4)} + \frac{2h^6}{6!} y_i^{(6)} + \frac{2h^8}{8!} y_i^{(8)} + O(h^{10}). \quad (12)$$

Now we have the relation:

$$y_{i-1}'' - 2y_i'' + y_{i+1}'' = \frac{2h^2}{2!} y_i^{(4)} + \frac{2h^4}{4!} y_i^{(6)} + \frac{2h^6}{6!} y_i^{(8)} + \frac{2h^8}{8!} y_i^{(10)} + O(h^{12}).$$

Substituting  $\frac{h^4}{12} y_i^{(6)}$  from the above equation in (12), we get

$$y_{i-1} - 2y_i + y_{i+1} = h^2 y_i'' + \frac{h^4}{12} y_i^{(4)} + \frac{h^2}{30} \left( y_{i-1}'' - 2y_i'' + y_{i+1}'' - h^2 y_i^{(4)} - \frac{h^6}{360} y_i^{(8)} \right) + \frac{2h^8}{8!} y_i^{(8)} + O(h^{10})$$

$$y_{i-1} - 2y_i + y_{i+1} = h^2 \left( y_i'' + \frac{1}{30} (y_{i-1}'' - 2y_i'' + y_{i+1}'') \right) + \frac{h^4}{12} y_i^{(4)} - \frac{h^4}{30} y_i^{(4)} - \frac{h^6}{10800} y_i^{(8)} + \frac{2h^8}{8!} y_i^{(8)} + O(h^{10})$$

$$y_{i-1} - 2y_i + y_{i+1} = h^2 \left( y_i'' + \frac{1}{30} \delta^2 y_i'' \right) + \frac{h^4}{20} y_i^{(4)} - \frac{13h^6}{302400} y_i^{(8)} + O(h^{10})$$

and

$$y_{i-1} - 2y_i + y_{i+1} = \frac{h^2}{30} (y_{i-1}'' + 28y_i'' + y_{i+1}'') + R, \quad (13)$$

where  $R = \frac{h^4}{20} y_i^{(4)} - \frac{13h^6}{302400} y_i^{(8)} + O(h^{10})$ .

Now from the equation (3), we have

$$\varepsilon y_{i+1}'' = -p_{i+1} y_{i+1}' - q_{i+1} y_{i+1} + f_{i+1} \quad (14)$$

$$\varepsilon y_i'' = -p_i y_i' - q_i y_i + f_i \quad (15)$$

$$\varepsilon y_{i-1}'' = -p_{i-1} y_{i-1}' - q_{i-1} y_{i-1} + f_{i-1}. \quad (16)$$

Using the following three-point approximations for first-order derivatives:

$$y_i' = \frac{y_{i+1} - y_{i-1}}{2h} \quad (17)$$

$$y_{i+1}' = \frac{3y_{i+1} - 4y_i + y_{i-1}}{2h} \quad (18)$$

$$y_{i-1}' = \frac{-y_{i+1} + 4y_i - 3y_{i-1}}{2h}. \quad (19)$$

Substituting (17), (18) and (19) in (14), (15) and (16) respectively, and simplifying (13), we get

$$\varepsilon \left( \frac{y_{i-1} - 2y_i + y_{i+1}}{h^2} \right) + \frac{p_{i-1}}{60h} (-3y_{i-1} + 4y_i - y_{i+1}) + \frac{28p_i}{60h} (y_{i+1} - y_{i-1}) + \frac{p_{i+1}}{60h} (y_{i-1} - 4y_i + 3y_{i+1}) + \frac{q_{i-1}}{30} y_{i-1} + \frac{28q_i}{30} y_i + \frac{q_{i+1}}{30} y_{i+1} = \frac{1}{30} (f_{i-1} + 28f_i + f_{i+1}).$$

Now introducing the fitting factor  $\sigma(\rho)$  in the above scheme, we have

$$\sigma(\rho) \varepsilon \left( \frac{y_{i-1} - 2y_i + y_{i+1}}{h^2} \right) + \frac{p_{i-1}}{60h} (-3y_{i-1} + 4y_i - y_{i+1}) + \frac{28p_i}{60h} (y_{i+1} - y_{i-1}) + \frac{p_{i+1}}{60h} (y_{i-1} - 4y_i + 3y_{i+1}) + \frac{q_{i-1}}{30} y_{i-1} + \frac{28q_i}{30} y_i + \frac{q_{i+1}}{30} y_{i+1} = \frac{1}{30} (f_{i-1} + 28f_i + f_{i+1}). \quad (20)$$

The fitting factor  $\sigma(\rho)$  is to be determined in such a way that the solution of difference scheme (20) converges uniformly to the solution of equation (3) with (2) and hence (1) with (2). Multiplying (20) by  $h$  and taking the limit as  $h \rightarrow 0$ , we get

$$\begin{aligned} \sigma(\rho)\varepsilon\left(\frac{y_{i-1}-2y_i+y_{i+1}}{h^2}\right)+\frac{p(0)}{60}(-3y_{i-1}+4y_i-y_{i+1})+\frac{28p(0)}{60}(y_{i+1}-y_{i-1})+ \\ \frac{p(0)}{60}(y_{i-1}-4y_i+3y_{i+1})=0. \end{aligned} \quad (21)$$

Let  $P = \frac{p^2(0) - \varepsilon q(0)}{p(0)}$ . By using (9), we get

$$\begin{aligned} \lim_{h \rightarrow 0} (y(ih-h) - 2y(ih) + y(ih+h)) &= (\alpha - y_0(0))e^{-Pi\rho} (e^{P\rho} + e^{-P\rho} - 2) \\ \lim_{h \rightarrow 0} (-3y(ih-h) + 4y(ih) - y(ih+h)) &= (\alpha - y_0(0))e^{-Pi\rho} (-3e^{P\rho} - e^{-P\rho} + 4) \\ \lim_{h \rightarrow 0} (y(ih-h) - 4y(ih) + 3y(ih+h)) &= (\alpha - y_0(0))e^{-Pi\rho} (e^{P\rho} + 3e^{-P\rho} - 4) \text{ and} \\ \lim_{h \rightarrow 0} (y(ih+h) - y(ih-h)) &= (\alpha - y_0(0))e^{-Pi\rho} (e^{-P\rho} - e^{P\rho}). \end{aligned}$$

By using the above equations in equation (21), we get

$$\frac{\sigma(\rho)}{\rho} (e^{P\rho} + e^{-P\rho} - 2) = -\frac{p(0)}{60} (-30e^{P\rho} + 30e^{-P\rho}).$$

$$\text{Therefore} \quad \sigma(\rho) = \frac{\rho p(0)}{2} \coth\left(\frac{(p^2(0) - \varepsilon q(0))\rho}{2p(0)}\right), \quad (22)$$

which is a required constant fitting factor  $\sigma(\rho)$ .

Finally, by making use of equation (20) and  $\sigma(\rho)$  given by equation (22), we get the following three-term recurrence relationship:

$$E_i y_{i-1} - F_i y_i + G_i y_{i+1} = R_i, \quad (i = 1, 2, 3, \dots, N-1), \quad (23)$$

where

$$\begin{aligned} E_i &= \frac{\sigma\varepsilon}{h^2} - \frac{3p_{i-1}}{60h} + \frac{q_{i-1}}{30} - \frac{28p_i}{60h} + \frac{p_{i+1}}{60h} \\ F_i &= \frac{2\sigma\varepsilon}{h^2} - \frac{4p_{i-1}}{60h} - \frac{28q_{i-1}}{30} + \frac{4p_{i+1}}{60h} \\ G_i &= \frac{\sigma\varepsilon}{h^2} - \frac{p_{i-1}}{60h} + \frac{q_{i+1}}{30} + \frac{28p_i}{60h} + \frac{3p_{i+1}}{60h} \\ R_i &= \frac{1}{30} (f_{i-1} + 28f_i + f_{i+1}) \end{aligned}$$

Equation (23) gives a system of  $(N-1)$  equations with  $(N-1)$  unknowns  $y_1$  to  $y_{N-1}$ . These  $(N-1)$  equations together with the Eq. (4) are sufficient to solve the obtained tri-diagonal system by using an efficient solver called 'Thomas Algorithm' described in [32].

We assume the matrix of this set of linear equations as  $D_N$ .

**Lemma:** For all  $\varepsilon > 0$  and all  $h = 1/N$ , the matrix  $D_N$  is an irreducible and diagonally dominant matrix.

**Proof.** Clearly,  $D_N$  is a tri-diagonal matrix. Hence,  $D_N$  is irreducible if its co-diagonals contain non zero elements only. It is easily seen that the co-diagonals  $E_i, G_i$  do not vanish for all  $\varepsilon > 0$ ,  $h > 0$  and  $\alpha_i \in R$ . Hence  $D_N$  is irreducible.

Since  $E_i, G_i$  do not vanish for all  $\varepsilon > 0$ ,  $h > 0$  and  $\alpha_i \in R$ , these expressions are of constant sign. Then obviously,  $E_i > 0, G_i > 0$ .

Now in each row of  $D_N$ , the modulus of the diagonal element is greater than or equal to the sum of the two off-diagonal elements for all  $i, (i=1,2,3,\dots,N-1)$ . This proves that  $D_N$  is diagonally dominant. Under the above-mentioned conditions, the 'Thomas Algorithm' is stable. The method of LU decomposition (or Gaussian elimination) which is equivalent to the "Thomas algorithm" provides a numerically stable technique for solving the system when the coefficient matrix of the system is diagonally dominant or irreducibly diagonally dominant and hence non-singular.

### 2.1.1. Description of the method for Right-End Boundary Layer Problems

To describe the method, we again consider the singularly perturbed boundary value problem (3) - (4) with  $p(x) \leq M < 0$ . The theory of singular perturbation provides the solution of (3) with (4) in the form (cf.[9], pp.22-26):

$$y(x) = y_0(x) + \frac{p(1)}{p(x)} (\beta - y_0(1)) e^{\int_x^1 \left( \frac{p(x) - q(x)}{\varepsilon p(x)} \right) dx} + o(\varepsilon), \quad (24)$$

where  $y_0(x)$  represents the solution of the reduced problem:

$$p(x)y_0'(x) + q(x)y_0(x) = f(x); y_0(0) = \alpha. \quad (25)$$

Expanding  $p(x)$  and  $q(x)$  in (24) with the help of Taylor's series about the point ' $x=1$ ' and restricting to their first terms, we obtain:

$$y(x) = y_0(x) + (\beta - y_0(1)) e^{\left( \frac{p(1) - q(1)}{\varepsilon p(1)} \right) (1-x)} + o(\varepsilon). \quad (26)$$

Further, considering equation (26) at the point  $x = x_i = ih, i = 0, 1, 2, \dots, N$  and taking the limit as  $h \rightarrow 0$  we obtain

$$\lim_{h \rightarrow 0} y(ih) = y_0(0) + (\beta - y_0(1)) e^{\left( \frac{p^2(1) - \varepsilon q(1)}{p(1)} \right) \left( \frac{1 - i\rho}{\varepsilon} \right)} + o(\varepsilon), \quad (27)$$

where  $\rho = h / \varepsilon$ .

Let  $\hat{P} = \frac{p^2(1) - \varepsilon q(1)}{p(1)}$ . By using (9), we get

$$\begin{aligned}\lim_{h \rightarrow 0} (y(ih-h) - 2y(ih) + y(ih+h)) &= (\beta - y_0(1)) e^{\hat{p} \left(\frac{1}{\varepsilon} - i\rho\right)} (e^{\hat{p}\rho} + e^{-\hat{p}\rho} - 2) \\ \lim_{h \rightarrow 0} (-3y(ih-h) + 4y(ih) - y(ih+h)) &= (\beta - y_0(1)) e^{\hat{p} \left(\frac{1}{\varepsilon} - i\rho\right)} (-3e^{\hat{p}\rho} - e^{-\hat{p}\rho} + 4) \\ \lim_{h \rightarrow 0} (y(ih-h) - 4y(ih) + 3y(ih+h)) &= (\beta - y_0(0)) e^{\hat{p} \left(\frac{1}{\varepsilon} - i\rho\right)} (e^{\hat{p}\rho} + 3e^{-\hat{p}\rho} - 4) \\ \lim_{h \rightarrow 0} (y(ih+h) - y(ih-h)) &= (\alpha - y_0(0)) e^{\hat{p} \left(\frac{1}{\varepsilon} - i\rho\right)} (e^{-\hat{p}\rho} - e^{\hat{p}\rho}).\end{aligned}$$

By using the above equations in equation (21), we get

$$\frac{\sigma(\rho)}{\rho} (e^{\hat{p}\rho} + e^{-\hat{p}\rho} - 2) = -\frac{p(0)}{60} (-30e^{\hat{p}\rho} + 30e^{-\hat{p}\rho})$$

Therefore, 
$$\sigma(\rho) = \frac{\rho p(0)}{2} \coth \left( \frac{(p^2(1) - \varepsilon q(1))\rho}{2p(1)} \right). \quad (28)$$

which is a required constant fitting factor. Using equation (20) with  $\sigma(\rho)$  given by equation (28), we have the three-term recurrence relationship (23).

### 3. STABILITY AND CONVERGENCE ANALYSIS

**Theorem 1:** Assuming the conditions  $\varepsilon > 0$ ,  $p(x) > M > 0$  and  $q(x) < 0, \forall x \in [0, 1]$ , the system of difference equations (23), along with the given boundary conditions, possesses a solution which is unique and satisfies

$$\|y\|_{h,\infty} \leq 2M^{-1} \|R\|_{h,\infty} + (|\eta| + |\gamma|),$$

where  $\|\cdot\|_{h,\infty}$  denotes the discrete  $l_\infty$  - norm, given by  $\|x\|_{h,\infty} = \max_{0 \leq i \leq N} \{|x_i|\}$ .

**Proof:** Let the difference operator given on the left-hand side of (14) is denoted by  $L_h(\cdot)$  and  $\omega_i$  represents any mesh function which satisfies  $L_h(\omega_i) = f_i$ . Rearranging the difference scheme (23) and using the condition that the coefficients of  $E_i, F_i$  and  $G_i$  are non-negative, we obtain

$$\begin{aligned}F_i |\omega_i| &\leq |R_i| + E_i |\omega_{i-1}| + G_i |\omega_{i+1}| \\ \Rightarrow \left( \frac{2\sigma\varepsilon}{h^2} - \frac{4p_{i-1}}{60h} - \frac{28q_{i-1}}{30} + \frac{4p_{i+1}}{60h} \right) |\omega_i| &\leq |R_i| + \left( \frac{\sigma\varepsilon}{h^2} - \frac{3p_{i-1}}{60h} + \frac{q_{i-1}}{30} - \frac{28p_i}{60h} + \frac{p_{i+1}}{60h} \right) |\omega_{i-1}| + \\ &\quad \left( \frac{\sigma\varepsilon}{h^2} - \frac{p_{i-1}}{60h} + \frac{q_{i+1}}{30} + \frac{28p_i}{60h} + \frac{3p_{i+1}}{60h} \right) |\omega_{i+1}| \\ \Rightarrow \sigma\varepsilon \left( \frac{|\omega_{i+1}| - 2|\omega_i| + |\omega_{i-1}|}{h^2} \right) &+ \frac{p_{i-1}}{30} \left( \frac{-|\omega_{i+1}| + 4|\omega_i| - 3|\omega_{i-1}|}{2h} \right) + \frac{q_{i-1}}{30} |\omega_{i-1}| + \frac{28q_i}{30} |\omega_i| + \frac{q_{i+1}}{30} |\omega_{i+1}| + \\ \Rightarrow \frac{28p_i}{30} \left( \frac{|\omega_{i+1}| - |\omega_{i-1}|}{2h} \right) &+ \frac{p_{i+1}}{30} \left( \frac{3|\omega_{i+1}| - 4|\omega_i| + |\omega_{i-1}|}{2h} \right) + |R_i| \geq 0.\end{aligned}$$



Now, taking the help of the assumptions  $\varepsilon > 0$  and  $p(x) > M$  and using the definition of  $l_\infty$  – norm the above inequality gets changed into

$$\sigma\varepsilon\left(\frac{|\omega_{i+1}|-2|\omega_i|+|\omega_{i-1}|}{h^2}\right)+\frac{M}{30}\left(\frac{-|\omega_{i+1}|-4|\omega_i|-3|\omega_{i-1}|}{2h}\right)+\frac{q_{i-1}}{30}|\omega_{i-1}|+\frac{28q_i}{30}|\omega_i|+\frac{q_{i+1}}{30}|\omega_{i+1}|+\frac{28M}{30}\left(\frac{|\omega_{i+1}|-|\omega_{i-1}|}{2h}\right)+\frac{M}{30}\left(\frac{3|\omega_{i+1}|-4|\omega_i|+|\omega_{i-1}|}{2h}\right)+|R_i|\geq 0. \tag{29}$$

To prove the uniqueness and existence of the solution, let  $\{u_i\}, \{v_i\}$  represents two sets of solutions of the difference equation (29) which satisfies the boundary conditions. Then  $\omega_i = u_i - v_i$  satisfies the condition  $L_h(\omega_i) = R_i$  where  $R_i = 0$  and  $\omega_0 = \omega_N = 0$ . Performing summation over  $i = 1, 2, \dots, N-1$ , in (29), we obtain

$$\begin{aligned} &\sum_{i=1}^{N-1} \sigma\varepsilon\left(\frac{|\omega_{i+1}|-2|\omega_i|+|\omega_{i-1}|}{h^2}\right)+\sum_{i=1}^{N-1} \frac{M}{30}\left(\frac{-|\omega_{i+1}|-4|\omega_i|-3|\omega_{i-1}|}{2h}\right)+\sum_{i=1}^{N-1} \frac{q_{i-1}}{30}|\omega_{i-1}|+\sum_{i=1}^{N-1} \frac{28q_i}{30}|\omega_i|+ \\ &\sum_{i=1}^{N-1} \frac{q_{i+1}}{30}|\omega_{i+1}|+\sum_{i=1}^{N-1} \frac{28M}{30}\left(\frac{|\omega_{i+1}|-|\omega_{i-1}|}{2h}\right)+\sum_{i=1}^{N-1} \frac{M}{30}\left(\frac{3|\omega_{i+1}|-4|\omega_i|+|\omega_{i-1}|}{2h}\right)+\sum_{i=1}^{N-1} |R_i|\geq 0 \\ \Rightarrow &-\sigma\varepsilon\frac{|\omega_1|}{h^2}-\sigma\varepsilon\frac{|\omega_{N-1}|}{h^2}+\|p\|_{h,\infty}\frac{|\omega_1|}{60h}+\|p\|_{h,\infty}\frac{3|\omega_{N-1}|}{60h}+\frac{1}{30}\sum_{i=1}^{N-1} q_{i-1}|\omega_{i-1}|+\frac{28}{30}\sum_{i=1}^{N-1} q_i|\omega_i|+ \\ &\frac{1}{30}\sum_{i=1}^{N-1} q_{i+1}|\omega_{i+1}|-\frac{28M}{60h}|\omega_1|-\frac{28M}{60h}|\omega_{N-2}|-\frac{3M}{60h}|\omega_1|-\frac{M}{60h}|\omega_{N-1}|+\sum_{i=1}^{N-1} |R_i|\geq 0. \end{aligned} \tag{30}$$

Since,  $\varepsilon > 0, \|p\|_{h,\infty} \geq 0, q_i < 0$  and  $|\omega_i| \geq 0, \forall i, i = 1, 2, \dots, N-1$ , therefore, for the inequality (30) to be true, we must have

$$\omega_i = 0 \forall i, i = 1, 2, \dots, N-1.$$

This implies that the solution of the tri-diagonal system of difference equations (23) is unique. In the case of linear equations, the uniqueness of the solution implies its existence.

Now to validate the estimate, let  $\omega_i = y_i - l_i$ , where  $y_i$  satisfies the difference equations (23) along with the boundary conditions and  $l_i = (1-ih)\eta + (ih)\gamma$ , then  $\omega_0 = \omega_N = 0$  and  $\omega_i, i = 1, 2, \dots, N-1$ .

Now, let  $|\omega_n| = \|\omega\|_{h,\infty} \geq |\omega_i|, i = 0, 1, 2, \dots, N$ . Then performing summation over (29) from  $i = n$  to  $N-1$  and taking the help of the assumption on  $p(x)$ , we obtain

$$\begin{aligned} &-\sigma\varepsilon\left(\frac{|\omega_n|-|\omega_{n-1}|}{h^2}\right)-\sigma\varepsilon\frac{|\omega_{N-1}|}{h^2}+\frac{M}{30}\left(\frac{-|\omega_{N-1}|-4|\omega_n|-3|\omega_{n-1}|}{2h}\right)+\frac{1}{30}\sum_{i=n}^{N-1} q_{i-1}|\omega_{i-1}|+\frac{28}{30}\sum_{i=n}^{N-1} q_i|\omega_i|+ \\ &\frac{1}{30}\sum_{i=n}^{N-1} q_{i+1}|\omega_{i+1}|+\frac{28M}{30}\left(\frac{|\omega_{N-1}|-|\omega_n|-|\omega_{n-1}|}{2h}\right)+\frac{M}{30}\left(\frac{-|\omega_{N-1}|-3|\omega_n|-|\omega_{n-1}|}{2h}\right)+\sum_{i=n}^{N-1} |R_i|\geq 0 \end{aligned} \tag{31}$$

Taking the condition on  $q(x)$  into consideration, inequality (28, 31) implies

$$\frac{M}{2} |\omega_n| \leq h \sum_{i=n}^{N-1} |R_i| \leq h \sum_{i=0}^N |h_i| \leq \|R\|_{h,\infty},$$

i.e. we have

$$|\omega_n| \leq 2M^{-1} \|R\|_{h,\infty} \quad (32)$$

Again, we have  $y_i = \omega_i + l_i$

$$\begin{aligned} \|y\|_{h,\infty} &= \max_{0 \leq i \leq N} \{|y_i|\} \leq \|\omega\|_{h,\infty} + \|l\|_{h,\infty} \\ &\leq \|\omega_n\| + \|l\|_{h,\infty}. \end{aligned} \quad (33)$$

Now to complete the proof of the estimate, the bound on  $l_i$  has to be found.

$$\begin{aligned} \|l\|_{h,\infty} &= \max_{0 \leq i \leq N} \{|l_i|\} \leq \max_{0 \leq i \leq N} \{|(1-ih)|\eta| + |ih|\gamma|\} \\ &\leq \max_{0 \leq i \leq N} \{|(1-ih)|\eta| + (ih)|\gamma|\} \end{aligned}$$

i.e., we have

$$\|l\|_{h,\infty} \leq |\eta| + |\gamma| \quad (34)$$

From equations (33)-(34), we obtain the estimate

$$\|y\|_{h,\infty} \leq 2M^{-1} \|R\|_{h,\infty} + (|\eta| + |\gamma|).$$

This theorem establishes the fact that the solution to the system of the difference equations (23) are uniformly bounded and is independent of the mesh size  $h$  and perturbation parameter  $\varepsilon$ . This proves the stability of the scheme for all step sizes.

**Corollary 1:** Under the conditions stated in theorem-1, the error  $e_i = y(x_i) - y_i$ , which occurs between  $y(x)$ , the solution of the continuous problem (3)-(4) and  $y_i$ , the solution of the discretized problem, together with boundary conditions, satisfies the estimate

$$\|e\|_{h,\infty} = 2M^{-1} \|\tau\|_{h,\infty},$$

Where  $|\tau_i| \leq \max_{x_{i-1} \leq i \leq x_{i+1}} \left\{ \frac{\sigma h^2 \varepsilon}{12} |y^{(4)}(x)| \right\} + \max_{x_{i-1} \leq i \leq x_{i+1}} \left\{ \frac{28 p h^2}{180} |y^{(3)}(x)| \right\}$

(The coefficients  $p(x), q(x)$  are assumed to be sufficiently differentiable to ensure that the solution  $y(x)$  belongs to  $C^3[0,1]$ ).

**Proof:** Truncation error in the difference scheme, denoted by  $\tau_i$ , is written as

$$\begin{aligned}
 \tau_i &= \sigma\varepsilon \left\{ \left( \frac{y_{i+1} - 2y_i + y_{i-1}}{h^2} \right) - y_i'' \right\} + \frac{p_{i-1}}{30} \left\{ \left( \frac{-3y_{i-1} + 4y_i - y_{i+1}}{2h} \right) - y_{i-1}' \right\} + \frac{28p_i}{30} \left\{ \left( \frac{y_{i+1} - y_{i-1}}{2h} \right) - y_i' \right\} + \\
 &\quad \frac{p_{i+1}}{30} \left\{ \left( \frac{y_{i-1} - 4y_i + 3y_{i+1}}{2h} \right) - y_{i+1}' \right\}. \\
 \Rightarrow \tau_i &= \sigma\varepsilon \left\{ \frac{h^2}{12} y_i^{(4)} + \frac{h^4}{360} y_i^{(6)} + \dots \right\} + \frac{p_{i-1}}{30} \left\{ -\frac{h^2}{3} y_i^{(3)} - \frac{h^3}{12} y_i^{(4)} + \dots \right\} + \frac{28p_i}{30} \left\{ \frac{h^2}{6} y_i^{(3)} + \frac{h^4}{120} y_i^{(5)} + \dots \right\} + \\
 &\quad \frac{p_{i+1}}{30} \left\{ -\frac{h^2}{3} y_i^{(3)} - \frac{h^3}{12} y_i^{(4)} + \dots \right\} \\
 \Rightarrow |\tau_i| &\leq \max_{x_{i-1} \leq i \leq x_{i+1}} \left\{ \frac{\sigma h^2 \varepsilon}{12} |y^{(4)}(x)| \right\} - \max_{x_{i-1} \leq i \leq x_{i+1}} \left\{ \frac{p h^3}{90} |y^{(3)}(x)| \right\} + \max_{x_{i-1} \leq i \leq x_{i+1}} \left\{ \frac{28 p h^2}{180} |y^{(3)}(x)| \right\} + \max_{x_{i-1} \leq i \leq x_{i+1}} \left\{ \frac{p h^3}{90} |y^{(3)}(x)| \right\} \\
 \Rightarrow |\tau_i| &\leq \max_{x_{i-1} \leq i \leq x_{i+1}} \left\{ \frac{\sigma h^2 \varepsilon}{12} |y^{(4)}(x)| \right\} + \max_{x_{i-1} \leq i \leq x_{i+1}} \left\{ \frac{28 p h^2}{180} |y^{(3)}(x)| \right\} \tag{35}
 \end{aligned}$$

It can be easily shown that the error  $e_i$  satisfies

$$L_h(e(x_i)) = L_h(y(x_i)) - L_h(y_i) = \tau_i, i = 1, 2, \dots, N-1$$

and  $e_0 = e_N = 0$ .

Then, Theorem-1 implies that

$$\|e\|_{h,\infty} \leq 2M^{-1} \|\tau\|_{h,\infty} \tag{36}$$

For fixed values of the parameter  $\varepsilon$ , the convergence of the difference scheme is established by the estimate (36).

**Theorem 2:** Under the assumptions  $\varepsilon > 0$ ,  $p(x) \leq M < 0$  and  $q(x) < 0, \forall x \in [0, 1]$ , the system of difference equations (23), along with the given boundary conditions, possesses a solution which is unique and satisfies

$$\|y\|_{h,\infty} \leq 2M^{-1} \|R\|_{h,\infty} + (|\eta| + |\gamma|)$$

where  $\|\cdot\|_{h,\infty}$  represents the discrete  $l_\infty$  - norm, given by  $\|x\|_{h,\infty} = \max_{0 \leq i \leq N} \{|x_i|\}$ .

The proof of estimate can be established in a similar manner as done in theorem 1.

#### 4. NUMERICAL ILLUSTRATIONS

In order to show the effectiveness of the proposed method, we have solved the two test example problems and presented the computational results in terms of maximum absolute errors. These test problems have been chosen because they have been widely discussed in the literature and the approximate solutions are available for comparison. The computational results are presented in Table 1 until Table 6 for various values of grid point  $N$  and perturbation parameter  $\varepsilon$ .

Note that the maximum absolute errors (MAE):  $E_\varepsilon^N$  are calculated by  $E_\varepsilon^N = \max_{0 \leq i \leq N} [|y(x_i) - y_i|]$ , where  $y(x_i)$  and  $y_i$  denote the exact and approximate solution respectively. Since the exact solutions of the problems are not known, the maximum absolute errors for the examples are calculated using the following double mesh principle  $E_\varepsilon^N = \max_{0 \leq i \leq N} [|y_i^N - y_i^{2N}|]$ . The computational rate of convergence is obtained by using the double mesh principle defined below:

Let  $Z_h = \max |y_j^h - y_j^{h/2}|, j = 1, \dots, N - 1$ , where  $y_j^h$  is the computed solution on the mesh  $\{x_j\}_0^N$  at the nodal point  $x_j$ , where  $x_j = x_{j-1} + h, j = 1, 2, \dots, N$  and  $y_j^{h/2}$  is the computed solution at the nodal point  $x_j$  on the mesh  $\{x_j\}_0^{2N}$ , where  $x_j = x_{j-1} + h/2, j = 1, 2, \dots, 2N$ . In the same way we can define  $Z_{h/2}$  by replacing  $h$  by  $h/2$  and  $N$  by  $2N$  i.e.,  $Z_{h/2} = \max |y_j^{h/2} - y_j^{h/4}|, j = 1, \dots, 2N - 1$ .

The computed rate of convergence is defined as  $R_\varepsilon^N = \frac{\log Z_h - \log Z_{h/2}}{\log(2)}$ .

We have find the computed rate of convergence for the example problems and the results are shown in Table 7 and Table 8. The computational rate of convergence agrees with the theoretical rate of convergence and the proposed method gives a second-order convergent.

**Problem 1:** First we consider the following constant-coefficient convection delayed dominated diffusion equation:

$$\varepsilon y''(x) + 5y'(x) + y(x - \delta) = 0; x \in [0, 1]$$

with interval boundary conditions  $y(x) = 1$  on  $-\delta \leq x \leq 0$  and  $y(1) = 0$ , which has a boundary layer at the left side of the domain near  $x = 0$ .

The exact solution of this example problem is given by:  $y(x) = \frac{\gamma - \eta e^{m_2}}{e^{m_1} - e^{m_2}} e^{m_1 x} + \frac{\eta e^{m_1} - \gamma}{e^{m_1} - e^{m_2}} e^{m_2 x}$

$$\text{where } m_1 = \frac{-(p - \delta q) + \sqrt{(p - \delta q)^2 - 4\varepsilon q}}{2\varepsilon}, m_2 = \frac{-(p - \delta q) - \sqrt{(p - \delta q)^2 - 4\varepsilon q}}{2\varepsilon}.$$

The computational results in terms of maximum absolute errors for Problem 1 are given in Tables 1, 2 and 3 for  $\delta = 0.1, \delta = 0.3 * \varepsilon$  and  $\delta = 0.5 * \varepsilon$ , respectively.

**Table 1** Maximum absolute errors for different values of  $N$  and  $\varepsilon$  with  $\delta = 0.1$  for the problem-1

$\varepsilon \downarrow$	$N = 8$	$N = 16$	$N = 32$	$N = 64$	$N = 128$	$N = 256$
$2^{-2}$	3.02393E-03	4.03771E-03	3.87004E-03	3.88572E-03	3.89066E-03	3.88840E-03
$2^{-3}$	1.05762E-03	1.48334E-03	1.99890E-03	1.91614E-03	1.92806E-03	1.92919E-03
$2^{-4}$	8.73248E-04	5.21208E-04	7.34664E-04	9.94653E-04	9.53466E-04	9.60916E-04
$2^{-5}$	8.71867E-04	4.31150E-04	2.58763E-04	3.65622E-04	4.96119E-04	4.75496E-04
$2^{-6}$	8.71870E-04	4.30487E-04	2.14248E-04	1.28916E-04	1.82368E-04	2.47687E-04
$2^{-7}$	8.71870E-04	4.30490E-04	2.13911E-04	1.06780E-04	6.43576E-05	9.10759E-05
$2^{-8}$	8.71870E-04	4.30490E-04	2.13914E-04	1.06628E-04	5.33440E-05	3.21586E-05

$2^{-9}$	8.71870E-04	4.30490E-04	2.13914E-04	1.06631E-04	5.32351E-05	2.66634E-05
$2^{-10}$	8.71870E-04	4.30490E-04	2.13914E-04	1.06631E-04	5.32382E-05	2.66004E-05
$2^{-12}$	8.71870E-04	4.30490E-04	2.13914E-04	1.06631E-04	5.32382E-05	2.66035E-05
$2^{-16}$	8.71870E-04	4.30490E-04	2.13914E-04	1.06631E-04	5.32382E-05	2.66035E-05
$2^{-32}$	8.71870E-04	4.30490E-04	2.13914E-04	1.06631E-04	5.32382E-05	2.66035E-05

**Table 2** Maximum absolute errors for different values of  $N$  and  $\varepsilon$  with  $\delta = 0.3 * \varepsilon$  for the problem-1

$\varepsilon \downarrow$	$N = 32$	$N = 64$	$N = 128$	$N = 256$	$N = 512$	$N = 1024$
$10^{-1}$	1.47474E-03	1.48383E-03	1.48931E-03	1.50031E-03	1.49804E-03	1.49792E-03
$10^{-2}$	2.09726E-04	1.05763E-04	8.17031E-05	1.30370E-04	1.52379E-04	1.48565E-04
$10^{-3}$	2.09620E-04	1.04496E-04	5.21722E-05	2.60666E-05	1.30188E-05	7.88132E-06
$10^{-4}$	2.09597E-04	1.04479E-04	5.21584E-05	2.60574E-05	1.30218E-05	6.50761E-06
$10^{-5}$	2.09566E-04	1.04449E-04	5.21283E-05	2.60276E-05	1.29920E-05	6.47786E-06
$10^{-6}$	2.09582E-04	1.04465E-04	5.21444E-05	2.60437E-05	1.30081E-05	6.49396E-06
$10^{-7}$	2.09603E-04	1.04485E-04	5.21651E-05	2.60644E-05	1.30288E-05	6.51465E-06
$10^{-8}$	2.09600E-04	1.04483E-04	5.21624E-05	2.60617E-05	1.30261E-05	6.51195E-06
$10^{-9}$	2.09600E-04	1.04482E-04	5.21622E-05	2.60614E-05	1.30258E-05	6.51168E-06
$10^{-10}$	2.09600E-04	1.04482E-04	5.21621E-05	2.60614E-05	1.30258E-05	6.51165E-06
$10^{-12}$	2.09600E-04	1.04482E-04	5.21621E-05	2.60614E-05	1.30258E-05	6.51165E-06
$10^{-15}$	2.09600E-04	1.04482E-04	5.21621E-05	2.60614E-05	1.30258E-05	6.51165E-06
$10^{-20}$	2.09600E-04	1.04482E-04	5.21621E-05	2.60614E-05	1.30258E-05	6.51165E-06
$10^{-30}$	2.09600E-04	1.04482E-04	5.21621E-05	2.60614E-05	1.30258E-05	6.51165E-06

**Table 3** Maximum absolute errors for different values of  $N$  and  $\varepsilon$  with  $\delta = 0.5 * \varepsilon$  for the problem-1

$\varepsilon \downarrow$	$N = 32$	$N = 64$	$N = 128$	$N = 256$	$N = 512$	$N = 1024$
$10^{-1}$	1.48876E-03	1.49423E-03	1.50222E-03	1.51142E-03	1.51065E-03	1.51050E-03
$10^{-2}$	2.09824E-04	1.05759E-04	8.18148E-05	1.30460E-04	1.52498E-04	1.48654E-04
$10^{-3}$	2.09601E-04	1.04473E-04	5.21471E-05	2.60404E-05	1.30197E-05	7.89575E-06
$10^{-4}$	2.09595E-04	1.04477E-04	5.21558E-05	2.60548E-05	1.30191E-05	6.50492E-06
$10^{-5}$	2.09576E-04	1.04458E-04	5.21376E-05	2.60368E-05	1.30012E-05	6.48713E-06
$10^{-6}$	2.09602E-04	1.04485E-04	5.21645E-05	2.60637E-05	1.30281E-05	6.51396E-06
$10^{-7}$	2.09605E-04	1.04487E-04	5.21671E-05	2.60664E-05	1.30308E-05	6.51665E-06
$10^{-8}$	2.09600E-04	1.04483E-04	5.21626E-05	2.60619E-05	1.30263E-05	6.51215E-06
$10^{-9}$	2.09600E-04	1.04482E-04	5.21622E-05	2.60614E-05	1.30258E-05	6.51170E-06
$10^{-10}$	2.09600E-04	1.04482E-04	5.21621E-05	2.60614E-05	1.30258E-05	6.51165E-06
$10^{-12}$	2.09600E-04	1.04482E-04	5.21621E-05	2.60614E-05	1.30258E-05	6.51165E-06
$10^{-15}$	2.09600E-04	1.04482E-04	5.21621E-05	2.60614E-05	1.30258E-05	6.51165E-06
$10^{-20}$	2.09600E-04	1.04482E-04	5.21621E-05	2.60614E-05	1.30258E-05	6.51165E-06
$10^{-30}$	2.09600E-04	1.04482E-04	5.21621E-05	2.60614E-05	1.30258E-05	6.51165E-06

**Problem 2:** Now, we consider the following constant-coefficient convection delayed dominated diffusion equation from:

$$\varepsilon y''(x) - 5y'(x) + 2y(x - \delta) = 0; x \in [0, 1]$$

with interval boundary conditions  $y(x) = 0$  on  $-\delta \leq x \leq 0$  and  $y(1) = 2$ , which has a boundary layer at the left side of the domain near  $x = 1$ . The exact solution of this example is not given. The computational results in terms of maximum absolute errors for the example in Problem 2 are given in Tables 4, 5 and 6 for  $\delta = 0.1$ ,  $\delta = 0.3 * \varepsilon$  and  $\delta = 0.5 * \varepsilon$ , respectively.

**Table 4** Maximum absolute errors for different values of  $N$  and  $\varepsilon$  with  $\delta=0.1$  for problem- 2

$\varepsilon \downarrow$	$N=8$	$N=16$	$N=32$	$N=64$	$N=128$	$N=256$
$2^{-3}$	3.10985E-03	1.17642E-03	3.35574E-04	7.40886E-05	1.65105E-05	1.00136E-05
$2^{-4}$	3.34127E-03	1.51792E-03	5.79402E-04	1.65939E-04	3.82066E-05	7.27177E-06
$2^{-5}$	3.36014E-03	1.63122E-03	7.50063E-04	2.87622E-04	8.26120E-05	1.81198E-05
$2^{-6}$	3.36014E-03	1.64030E-03	7.50063E-04	3.72832E-04	1.43260E-04	4.13656E-05
$2^{-7}$	3.36024E-03	1.64036E-03	8.10560E-04	4.00718E-04	1.85880E-04	7.14660E-05
$2^{-8}$	3.36024E-03	1.64036E-03	8.10586E-04	4.02911E-04	1.99774E-04	9.28054E-05
$2^{-9}$	3.36024E-03	1.64036E-03	8.10586E-04	4.02925E-04	2.00854E-04	9.97361E-05
$2^{-10}$	3.36024E-03	1.64036E-03	8.10586E-04	4.02925E-04	2.00862E-04	1.00262E-04
$2^{-12}$	3.36024E-03	1.64036E-03	8.10586E-04	4.02925E-04	2.00862E-04	1.00267E-04
$2^{-16}$	3.36024E-03	1.64036E-03	8.10586E-04	4.02925E-04	2.00862E-04	1.00267E-04
$2^{-32}$	3.36024E-03	1.64036E-03	8.10586E-04	4.02925E-04	2.00862E-04	1.00267E-04

**Table 5** Maximum absolute errors for different values of  $N$  and  $\varepsilon$  and  $\delta=0.3*\varepsilon$  for the problem-2

$\varepsilon \downarrow$	$N=32$	$N=64$	$N=128$	$N=256$	$N=512$	$N=1024$
$10^{-1}$	4.16249E-04	9.45330E-05	2.49743E-05	5.78165E-06	3.27826E-05	3.99351E-06
$10^{-2}$	8.42048E-04	4.10273E-04	1.78698E-04	6.16014E-05	1.53184E-05	4.23193E-06
$10^{-3}$	8.43312E-04	4.19100E-04	2.08906E-04	1.04270E-04	5.16622E-05	2.38419E-05
$10^{-4}$	8.43449E-04	4.19189E-04	2.08973E-04	1.04338E-04	5.21380E-05	2.60674E-05
$10^{-5}$	8.43385E-04	4.19122E-04	2.08903E-04	1.04267E-04	5.20667E-05	2.59958E-05
$10^{-6}$	8.43418E-04	4.19153E-04	2.08934E-04	1.04298E-04	5.20977E-05	2.60268E-05
$10^{-7}$	8.43431E-04	4.19166E-04	2.08947E-04	1.04311E-04	5.21104E-05	2.60394E-05
$10^{-8}$	8.43441E-04	4.19177E-04	2.08947E-04	1.04322E-04	5.21212E-05	2.60502E-05
$10^{-9}$	8.43443E-04	4.19178E-04	2.08959E-04	1.04323E-04	5.21222E-05	2.60513E-05
$10^{-10}$	8.43443E-04	4.19178E-04	2.08959E-04	1.04323E-04	5.21224E-05	2.60514E-05
$10^{-12}$	8.43443E-04	4.19178E-04	2.08959E-04	1.04323E-04	5.21224E-05	2.60514E-05
$10^{-15}$	8.43443E-04	4.19178E-04	2.08959E-04	1.04323E-04	5.21224E-05	2.60514E-05
$10^{-20}$	8.43443E-04	4.19178E-04	2.08959E-04	1.04323E-04	5.21224E-05	2.60514E-05
$10^{-30}$	8.43443E-04	4.19178E-04	2.08959E-04	1.04323E-04	5.21224E-05	2.60514E-05

**Table 6** Computational results in terms of Maximum absolute errors for different values of  $N$  and  $\varepsilon$  and  $\delta=0.5*\varepsilon$  for the problem- 2

$\varepsilon \downarrow$	$N=32$	$N=64$	$N=128$	$N=256$	$N=512$	$N=1024$
$10^{-1}$	4.15653E-04	9.51290E-05	2.48551E-05	5.72205E-06	3.13520E-05	7.21216E-06
$10^{-2}$	8.41315E-04	4.09924E-04	1.78579E-04	6.16610E-05	1.53780E-05	2.98023E-06
$10^{-3}$	8.43257E-04	4.19079E-04	2.08903E-04	1.04275E-04	5.16589E-05	2.36854E-05
$10^{-4}$	8.43357E-04	4.19101E-04	2.08887E-04	1.04253E-04	5.20531E-05	2.59827E-05
$10^{-5}$	8.43444E-04	4.19180E-04	2.08962E-04	1.04325E-04	5.21250E-05	2.60541E-05
$10^{-6}$	8.43433E-04	4.19169E-04	2.08950E-04	1.04314E-04	5.21131E-05	2.60421E-05
$10^{-7}$	8.43422E-04	4.19158E-04	2.08939E-04	1.04303E-04	5.21023E-05	2.60314E-05
$10^{-8}$	8.43441E-04	4.19176E-04	2.08957E-04	1.04321E-04	5.21204E-05	2.60494E-05
$10^{-9}$	8.43442E-04	4.19178E-04	2.08959E-04	1.04323E-04	5.21222E-05	2.60512E-05
$10^{-10}$	8.43443E-04	4.19178E-04	2.08959E-04	1.04323E-04	5.21223E-05	2.60514E-05
$10^{-12}$	8.43443E-04	4.19178E-04	2.08959E-04	1.04323E-04	5.21224E-05	2.60514E-05
$10^{-15}$	8.43443E-04	4.19178E-04	2.08959E-04	1.04323E-04	5.21224E-05	2.60514E-05
$10^{-20}$	8.43443E-04	4.19178E-04	2.08959E-04	1.04323E-04	5.21224E-05	2.60514E-05
$10^{-30}$	8.43443E-04	4.19178E-04	2.08959E-04	1.04323E-04	5.21224E-05	2.60514E-05

**Table 7** The Rate of convergence  $R_\epsilon^N$  for various values of  $N$  and  $\epsilon$  and  $\delta = 0.5 * \epsilon$  for the problem 1

$\epsilon \downarrow$	$N=8$	$N=16$	$N=32$	$N=64$	$N=128$	$N=256$	$N=512$
$10^{-3}$	7.294E-07	1.779E-07	4.393E-08	1.091E-08	2.719E-09	6.783E-10	1.666E-10
$R_\epsilon^N$	2.0356	2.0178	2.0096	2.0045	2.0031	2.0255	
$10^{-4}$	7.293E-07	1.779E-07	4.393E-08	1.092E-08	2.720E-09	6.789E-10	1.695E-10
$R_\epsilon^N$	2.0354	2.0178	2.0082	2.0053	2.0023	2.0019	
$10^{-5}$	7.293E-07	1.779E-07	4.392E-08	1.091E-08	2.718E-09	6.779E-10	1.690E-10
$R_\epsilon^N$	2.0354	2.0181	2.0092	2.0050	2.0034	2.0040	
$10^{-6}$	7.293E-07	1.779E-07	4.393E-08	1.092E-08	2.721E-09	6.793E-10	1.697E-10
$R_\epsilon^N$	2.0354	2.0178	2.0082	2.0048	2.0020	2.0011	
$10^{-7}$	7.293E-07	1.779E-07	4.393E-08	1.092E-08	2.721E-09	6.795E-10	1.698E-10
$R_\epsilon^N$	2.0354	2.0178	2.0082	2.0048	2.0016	2.0006	
$10^{-8}$	7.293E-07	1.779E-07	4.393E-08	1.092E-08	2.721E-09	6.792E-10	1.697E-10
$R_\epsilon^N$	2.0354	2.0178	2.0082	2.0048	2.0022	2.0008	
$10^{-9}$	7.293E-07	1.779E-07	4.393E-08	1.092E-08	2.721E-09	6.792E-10	1.697E-10
$R_\epsilon^N$	2.0354	2.0178	2.0082	2.0048	2.0022	2.0008	
$10^{-10}$	7.293E-07	1.779E-07	4.393E-08	1.092E-08	2.721E-09	6.792E-10	1.697E-10
$R_\epsilon^N$	2.0354	2.0178	2.0082	2.0048	2.0022	2.0008	
$10^{-15}$	7.293E-07	1.779E-07	4.393E-08	1.092E-08	2.721E-09	6.792E-10	1.697E-10
$R_\epsilon^N$	2.0354	2.0178	2.0082	2.0048	2.0022	2.0008	

**Table 8** The Rate of convergence  $R_\epsilon^N$  for various values of  $N$  and  $\epsilon$  and  $\delta = 0.3 * \epsilon$  for the problem 2

$\epsilon \downarrow$	$N=8$	$N=16$	$N=32$	$N=64$	$N=128$	$N=256$	$N=512$
$10^{-3}$	6.134E-06	1.458E-06	3.557E-07	8.783E-08	2.182E-08	5.438E-09	7.287E-09
$R_\epsilon^N$	2.0728	2.0353	2.0179	2.0091	2.0045	0.4222	
$10^{-4}$	6.135E-06	1.459E-06	3.558E-07	8.787E-08	2.184E-08	5.443E-09	1.359E-09
$R_\epsilon^N$	2.0721	2.0358	2.0176	2.0084	2.0045	2.0019	
$10^{-5}$	6.135E-06	1.458E-06	3.557E-07	8.784E-08	2.182E-08	5.436E-09	1.355E-09
$R_\epsilon^N$	2.0731	2.0353	2.0177	2.0092	2.0050	2.0043	
$10^{-6}$	6.135E-06	1.459E-06	3.558E-07	8.785E-08	2.183E-08	5.439E-09	1.357E-09
$R_\epsilon^N$	2.0721	2.0358	2.0180	2.0087	2.0049	2.0029	
$10^{-7}$	6.135E-06	1.459E-06	3.558E-07	8.786E-08	2.183E-08	5.441E-09	1.358E-09
$R_\epsilon^N$	2.0721	2.0358	2.0178	2.0089	2.0044	2.0024	
$10^{-8}$	6.135E-06	1.459E-06	3.558E-07	8.786E-08	2.183E-08	5.442E-09	1.358E-09
$R_\epsilon^N$	2.0721	2.0358	2.0178	2.0089	2.0041	2.0027	
$10^{-9}$	6.135E-06	1.459E-06	3.558E-07	8.786E-08	2.183E-08	5.442E-09	1.358E-09
$R_\epsilon^N$	2.0721	2.0358	2.0178	2.0089	2.0041	2.0027	
$10^{-10}$	6.135E-06	1.459E-06	3.558E-07	8.786E-08	2.183E-08	5.442E-09	1.358E-09
$R_\epsilon^N$	2.0721	2.0358	2.0178	2.0089	2.0041	2.0027	
$10^{-15}$	6.135E-06	1.459E-06	3.558E-07	8.786E-08	2.183E-08	5.442E-09	1.358E-09
$R_\epsilon^N$	2.0721	2.0358	2.0178	2.0089	2.0041	2.0027	

## 5. DISCUSSIONS AND CONCLUSIONS

We have examined a three-point exponentially fitted second-order numerical method for singularly perturbed delayed boundary value problem having boundary layer at one end of the

considered region. Introduction of a fitting factor in a second-order finite difference scheme was made to take care of the rapid changes occurring in the boundary layer. The existence and uniqueness of the discrete problem along with stability estimates are discussed. We have presented maximum absolute errors for the standard examples chosen from the literature and also presented maximum absolute errors for some of the examples to show the efficiency of the method when  $\varepsilon \ll N$ . The computational results are presented in Tables 1-6. It is observed that the MAE for the problem is becoming uniform, when singular perturbation parameter  $\varepsilon \rightarrow 0$ , for any fixed value of  $N = \frac{1}{h}$ . If the value of  $\delta$  is small, for any fixed value of  $N = \frac{1}{h}$ , the maximum absolute error decreases. Tables show that the method presented in this paper is capable of producing second-order accurate results on uniform mesh with minimal computational effort. The main feature of the proposed fitted scheme is that it is independent of the very fine mesh size like Shishkin mesh.

## REFERENCES

- [1] Rihan, F. A. "Delay differential equations in biosciences: parameter estimation and sensitivity analysis. In Recent Advances in Applied Mathematics and Computational Methods," Proceedings of the 2013 International Conference on Applied Mathematics and Computational Methods (Venice, Italy September 2013) (2013) 50-58.
- [2] Stein, R. B., A theoretical analysis of neuronal variability: *Biophysical Journal* **5**, 2 (1965) 173-194.
- [3] Stein, R. B., Some models of neuronal variability: *Biophysical Journal* **7**, 1 (1967) 37-68.
- [4] Longtin, A., Milton, J. G., Complex oscillations in the human pupil light reflex with mixed and delayed feedback: *Mathematical Biosciences*, **90**, 1-2 (1988) 183-199.
- [5] Derstine, M. W., Gibbs, H. M., Hopf, F. A., Kaplan, D. L., Bifurcation gap in a hybrid optically bistable system: *Physical Review A* **26**, 6 (1982) 3720.
- [6] Bocharov, G. A., Rihan, F. A., Numerical modelling in biosciences using delay differential equations: *Journal of Computational and Applied Mathematics* **125**, 1-2 (2000) 183-199.
- [7] Nelson, P. W., Perelson, A. S., Mathematical analysis of delay differential equation models of HIV-1 infection: *Mathematical Biosciences* **179**, 1 (2002) 73-94.
- [8] Mackey, M. C., Glass, L., Oscillation and chaos in physiological control systems: *Science* **197**, 4300 (1977) 287-289.
- [9] R. E. O'Malley, "Singular Perturbation Methods for Ordinary Differential Equations". Applied Mathematical Sciences, 89, Springer, Berlin, (1990).
- [10] Knowles, K., Messick, R.E., On a class of singular perturbation problems: *J. Math. Anal. Appl.* **9** (1964) 42-58.
- [11] R. R., Gold, Magneto hydrodynamic pipe flow: Part I. *J. Fluid Mech.* **13**, (1962) pp. 505-512.
- [12] Kaushik, A., Singular perturbation analysis of bistable differential equation arising in the nerve pulse propagation: *Nonlinear Anal.* **09** (2008) 2106-2127.
- [13] Kaushik, A., Sharma, M. D., Numerical analysis of a mathematical model for propagation of an electrical pulse in a neuron: *Numer. Methods Partial Differ. Equ.* **27** (2008) 1-18.
- [14] Kadalbajoo, M. K., Sharma, K. K., Numerical treatment of a mathematical model arising from a model of neuronal variability: *J. Math. Anal. Appl.* **307**, (2005) 606-627.
- [15] Kaushik, A., Nonstandard perturbation approximation and traveling wave solutions of non-linear reaction diffusion equations: *Numer. Methods Partial Differ. Equ.* **24** (2008) 217-238.
- [16] R. E. O'Malley, "Introduction to Singular Perturbations," Academic Press, New York, (1974).
- [17] J. J. H. Miller., "Singular Perturbation Problems in Chemical Physics, Analytic and Computational Methods," XCVII Wiley, New York, (1997).
- [18] Lange, C. G., Miura, R.M., Singular perturbation analysis of boundary value problems for differential-difference equations. V. Small shifts with layer behavior: *SIAM Journal on Applied Mathematics* **54** (1994) 249-272.



- [19] Lange, C. G., Miura, R.M., Singular perturbation analysis of boundary value problems for differential-difference equations: *SIAM Journal on Applied Mathematics* **42** (1982) 502-531.
- [20] Lange, C. G., Miura, R.M., Singular Perturbation Analysis of Boundary Value Problems for Differential-Difference Equations. IV. A Nonlinear Example with Layer Behavior: *Studies in Applied Mathematics* **84** (1991) 231-273.
- [21] Kadalbajoo, M. K., Sharma, K. K., An  $\varepsilon$ -uniform fitted operator method for solving boundary-value problems for singularly perturbed delay differential equations: Layer behavior: *International journal of computer mathematics* **80** (2003) 1261-1276.
- [22] Kadalbajoo, M. K., Sharma, K. K., A numerical method based on finite difference for boundary value problems for singularly perturbed delay differential equations: *Applied Mathematics and Computation* **197** (2008) 692-707.
- [23] Sharma, M., Kaushik, A., Li, C., Analytic approximation to delayed convection dominated systems through transforms: *Journal of Mathematical Chemistry* **52** (2014) 2459-2474.
- [24] Swamy, D. K., Phaneendra, K., Babu, A. B., Reddy, Y. N., Computational method for singularly perturbed delay differential equations with twin layers or oscillatory behavior: *Ain Shams Engineering Journal* **6**, 1 (2015) 391-398.
- [25] Kanth, A. S. V., Kumar, P. M. M., Numerical treatment for a singularly perturbed convection delayed dominated diffusion equation via tension splines: *International Journal of Pure and Applied Mathematics* **113**, 6 (2017) 110 – 118.
- [26] File, G., Gadisa, G., Aga, T., Reddy, Y. N., Numerical solution of singularly perturbed delay reaction-diffusion equations with layer or oscillatory behavior: *American Journal of Numerical Analysis* **5**, 1 (2017) 1-10.
- [27] Chakravarthy, P. P., Kumar, K., A novel method for singularly perturbed delay differential equations of reaction-diffusion type: *Differential Equations and Dynamical Systems* **25**, (2017) 1-12.
- [28] Sirisha, C. L., Reddy, Y. N., Numerical integration of singularly perturbed delay differential equations using exponential integrating factor: *Mathematical Communications* **22**, 2 (2017) 251-264.
- [29] Mahendran, R., & Subburayan, V., Fitted finite difference method for third order singularly perturbed delay differential equations of convection diffusion type: *International Journal of Computational Methods* **16**, 5 (2019) 1840007 (17 pages).
- [30] Kanth, A. R., Kumar, P. M. M., Numerical method for a class of nonlinear singularly perturbed delay differential equations using parametric cubic spline. *International Journal of Nonlinear Sciences and Numerical Simulation* **19**, 3-4 (2018) 357-365.
- [31] Vaid, M.K, Arora, G., Solution of second order singularly perturbed delay differential equation using trigonometric B-Spline, *International Journal of Mathematical, Engineering and Management Sciences* **4**, 2 (2019) 349-360.
- [32] Chakravarthy, P. P., Kumar, S.D., Rao, R. N., An exponentially fitted finite difference scheme for a class of singularly perturbed delay differential equations with large delays, *Ain Shams Engineering Journal* **8**, (2017) 663-671.

